

Appl. No. 10/661,735
Amdt. Date May 23, 2005
Reply to the Office Action of February 22, 2005

AMENDMENTS TO THE CLAIMS

Claim 1 (currently amended): A hard tray for socket connectors each having a pick up cap mounted thereon, the pick up cap defining a top surface, the hard tray comprising:

a bracket body defining having a plurality of first spacers and a plurality of second spacers perpendicular to the first spacers, two adjacent first spacers and two adjacent second spacers cooperatively defining an opening an array of openings, each of the openings being configured to adapt for receiving a corresponding socket connector therein;

wherein the bracket body defines a bottom portion in the opening, the bottom portion defines a rough bottom surface, in use, the hard tray is stacked on another hard tray which has the same configuration as the hard tray, when the hard tray is needed to be removed from said another hard tray, the rough bottom surface is configured to have enough rough characteristics, thereby rough enough so as to prevent the bottom surface from sucking a corresponding the top surface of the pick up cap mounted a corresponding socket connector received said another hard tray.

Claim 2 (currently amended): The hard tray of claim 1, wherein the bracket body further has a plurality of first and second spacers perpendicular to each other, the first and second spacers being configured to support socket connectors received in corresponding openings at least one of the adjacent first spacers has a first extending portion extending into the opening.

Claim 3 (currently amended): The hard tray of claim 2, wherein at least one of the adjacent first spacers has a first extending portion extending into the opening, the first extending portion defines defining a top surface first

Appl. No. 10/661,735

Amdt. Date May 23, 2005

Reply to the Office Action of February 22, 2005

face higher than the bottom portion.

Claim 4 (original): The hard tray of claim 3, wherein at least one of the adjacent second spacers has a second extending portion extending into the opening.

Claim 5 (currently amended): The hard tray of claim 4, wherein the second extending portion defines a top ~~surface~~ second face coplanar with the top ~~surface~~ first face of the first extending portion.

Claim 6 (currently amended): The hard tray of claim ~~[[5]]~~ 1, wherein the openings at symmetrically opposite ends of the bracket body are partly closed by corresponding bottom portions.

Claim 7 (original): The hard tray of claim 6, wherein the remaining openings of the bracket body are fully closed by corresponding bottom portions.

Claim 8 (original): The hard tray of claim 7, wherein the bracket body defines a pair of ear portions at opposite ends thereof.

Claim 9 (original): In combination,

a plurality of hard trays closely stacked with one another, each of said hard trays defining a plurality of upward openings; and

a plurality of electronic parts disposed in the corresponding openings, respectively, each of said electronic parts defining an upward top plane for suction,

the hard tray defining a bottom portion under each of said openings, said bottom portion closely facing downwardly toward the upward top plane of another electronic part disposed in the corresponding opening of another hard tray under said hard tray; wherein

a bottom surface of said bottom portion is not smoothly planar so as not to result in improper suction between the bottom portion and the upward top plane of said another electronic part when the upward top plane of

Appl. No. 10/661,735

Amdt. Date May 23, 2005

Reply to the Office Action of February 22, 2005

said electronic part is suctioned by a nozzle for displacement of said electronic part.

Claim 10 (original): The combination of claim 9, wherein said bottom surface of said bottom portion is provided with a plurality of tiny protrusions to be in a rough form.

Claim 11 (currently amended): A hard tray for holding electronic parts equipped with a planar top surface for suction, comprising:

a bracket body having a plurality of spacers commonly defining a plurality of upward openings for holding said electronic parts therein; and the bracket body ~~defines~~ defining a bottom portion under each of the opening, the bottom portion ~~defines~~ defining a bottom surface which is configured to be not smoothly planar but with either recesses or openings therein for preventing suction derived from a plane vs. plane structure between the bottom surface and the planar top surface of another electronic part located right below said bottom portion.

Claim 12 (original): The hard tray of claim 11, wherein said bottom surface is roughed to provide said recesses from a micro-viewpoint.

Claim 13 (new): The combination of claim 9, wherein the openings at symmetrically opposite ends of each of the hard trays are partly closed by corresponding bottom portions.

Claim 14 (new): The combination of claim 13, wherein the remaining openings of said each of the hard trays are fully closed by corresponding bottom portions.

Claim 15 (new): The hard tray of claim 11, wherein the openings at symmetrically opposite ends of the bracket body are partly closed by corresponding bottom portions.

Claim 16 (new): The hard tray of claim 15, wherein the remaining openings of the

Appl. No. 10/661,735

Amdt. Date May 23, 2005

Reply to the Office Action of February 22, 2005

bracket body are fully closed by corresponding bottom portions.